

# Huawei FusionServer X6000 High-Density Server



Copyright © Huawei Technologies Co., Ltd. 2016. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

#### Trademark Notice

 HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective owners.

#### General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

#### HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base  
Bantian Longgang  
Shenzhen 518129, P.R. China  
Tel: +86-755-28780808  
Version No.: M3-041247-20161102-C-2.0

[www.huawei.com](http://www.huawei.com)

HUAWEI TECHNOLOGIES CO., LTD.



# Huawei FusionServer X6000 High-Density Server



## Ultra-High Density Design Reducing Equipment Footprint

- Provides a computing density twice that of a conventional 1U rack server, significantly maximizing space utilization in the equipment room.
- Accommodates four compute nodes in a 2U chassis with up to twenty-four 2.5-inch NVMe SSDs.

## Unified Management and Easy Maintenance

- Provides a unified management port for managing the entire chassis and all nodes, enabling easier deployment and maintenance.
- Adopts a modular design and hot-swappable key components such as hard disks, fan modules, and power supply units (PSUs), greatly improving O&M efficiency.

## Shared Architecture and High Energy Efficiency

- Enables server nodes to share two PSUs and four fan modules, which improves resource utilization and reduces energy consumption.
- Uses Huawei Dynamic Energy Management Technology (DEMT) to intelligently adjust energy consumption.

## Product Specifications

Form Factor	2U multi-node server
Server Nodes	4 half-width server nodes
Power Supply Units	2 hot-swappable 1500 W AC PSUs in 1+1 redundancy mode* Support 220V~240V AV or 240V HVDC
Fan Modules	4 hot-swappable fan modules in N+1 redundancy mode**
Power Supply	110 V to 220 V AC
Operating Temperature	5°C - 35°C (41°F - 95°F)
Certification	CE, UL, FCC, CCC, VCCI, and RoHS
Dimensions (H x W x D)	86.1 mm x 436 mm x 805 mm (3.39-in. x 17.17-in. x 31.69-in.)

\* Support for PSU 1+1 redundancy is subject to chassis configuration and power consumption.

\*\* Holding rails and cable racks are required to implement fan module hot swap

Huawei FusionServer X6000 is a high-density server that Huawei developed for the data center scale-out architecture. With an optimized density design, the X6000 improves data center space utilization and investment efficiency, and is ideal for service scenarios such as cloud computing, web applications, and high-performance computing (HPC).

# Huawei XH321 V3 Server Node



## Outstanding Computing Performance for Diverse Computing Scenarios

- Supports Intel® Xeon® E5-2600 v3/v4 series processors with each supporting up to twenty-two cores and 55 MB L3 cache capacity.

## Full NVMe SSD Storage

- Supports up to six 2.5-inch NVMe SSDs and delivers an ultra-high 4.8 million IOPS, significantly improving storage performance.

## Easy Installation and O&M

- Adopts a modular design. Provides pluggable modules for quicker deployment, easier maintenance, and shorter service rollout time.
- Uses Huawei's eSight comprehensive O&M solution, implementing batch OS deployment and batch BIOS, BMC, and RAID configuration.

The XH321 V3 is a new-generation half-width 2-socket server node for the Huawei X6000 high-density server. Powered by Intel® Xeon® E5-2600 v3/v4 series processors, it supports sixteen DDR4 DIMMs and is ideal for server applications, such as cloud computing, web applications, and HPC.

## Product Specifications

Form Factor	Half-width server node
Processors	1/2 Intel® Xeon® E5-2600 v3/v4 series processors
Memory	16 DDR4 DIMMs
Internal Storage	6 x 2.5-inch SATA/SAS HDDs or NVMe/SAS/SATA SSDs
LOM Network Ports	2 GE or 2 GE + 2 x 10GE
PCIe Expansion	Up to 2 PCIe slots
Management	Supports SNMP and IPMI. Provides virtual KVM, virtual media, SOL, remote control, hardware monitoring, and intelligent power supply. Adopts the power capping technology and independent management network ports, and supports NC-SI.
Operating Systems	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, CentOS, Citrix XenServer, VMware ESXi
Operating Temperature	5°C - 35°C (41°F - 95°F)
Certification	CE, UL, FCC, CCC, VCCI, and RoHS
Dimensions (H x W x D)	40.5 mm x 177.9 mm x 545.5 mm (1.59-in. x 7.00-in. x 21.48-in.)

Note: The operating systems supported are subject to the compatibility table.